

**PRODUCT  
DATA SHEET**

**DESIGN 260**  
Vinyl Collection 2011

January 2011

**Type of flooring**

**EN 653**

**Vinyl Floorcovering**

**Class of use**

**EN 685**



**23**



**31**

**Class**

**Description**



**EN 428**

**2,60 mm**



**EN 429**

**0,25 mm**



**EN 660-2**

Abrasion group

**T**



**EN 430**

**1,610 kg/m<sup>2</sup>**



**EN 426**

**30 m  
4+3+2m**



**EN ISO 717/2**

Impact sound  
absorption

**19 dB**



**EN 433**

Static  
indentation

**≤ 0,35 mm**

**Optional Characteristics**



**ISO 105/B02**

Light fastness

**≥ 6**



**EN 1815**

Static electrical  
propensity

**≤ 2 kV**



**Fire Classification**

EN 13501-1

Report N° :

**Bfl-s1  
RA10-0251**



**EN 434**

Dimensional  
stability

**≤ 0,40 %**



**Recyclable**

**OK**



**EN 423**

Chemical  
resistance

**OK**



**Slip resistance**

EN 13893  
DIN 51130

**≥ 0,30 μ  
R9**



**EN 12524**

Thermal resistance  
for underfloor heating

**0,04 m<sup>2</sup>/kW**



**EN 14041 : 2004**

**Manufactured in EEC by  
TARKETT**

